


DA-CHERRYBIRCH

Park and Street Luminaires


Description:

Pole-mounted LED park luminaire
 Light distribution type: direct
 Optical system: frosted polycarbonate diffuser, impact resistant
 Housing: aluminium
 Colour: dark grey (RAL7043)

General data:

Mains voltage: 220-240V, 0/50-60Hz (G663: 220-240V, 50-60Hz)
 LED lifetime, h: 50000/L80B10
 SDCM: 3
 Protection class IEC: I (II optional)
 Ingress protection code: IP65
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -25...+40

Installation:


With three screws on poles Ø60mm. Cable, 3.0m, 3x0.75mm²

Environment:

Outdoor

Application:

Park, public space



Photocell PCA switches lighting fixtures ON or OFF, at the same time it can be mounted into IP protected light fitting serving as a standalone solution. The built-in photo-sensor records the brightness of the surroundings and switches the connected lighting fixtures on at dusk and of again at dawn. Technical data: IP65- dust and waterproof, 35 lux, 1:05 ratio. For more information see the option list.

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
DA-CHERRYBIRCH-420-19W-30-	420	420	420	2536	18,6	136	80+	3000	4,9
DA-CHERRYBIRCH-420-26W-30-	420	420	420	3455	26,3	131	80+	3000	4,9
DA-CHERRYBIRCH-420-34W-30-	420	420	420	4318	34,4	126	80+	3000	4,9
DA-CHERRYBIRCH-420-41W-30-	420	420	420	4962	41,2	120	80+	3000	4,9
DA-CHERRYBIRCH-420-19W-40-	420	420	420	2655	18,6	143	80+	4000	4,9
DA-CHERRYBIRCH-420-26W-40-	420	420	420	3617	26,3	138	80+	4000	4,9
DA-CHERRYBIRCH-420-34W-40-	420	420	420	4521	34,4	131	80+	4000	4,9
DA-CHERRYBIRCH-420-41W-40-IP65	420	420	420	5195	41,2	126	80+	4000	4,9

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. icLighting is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

T830 Colour temperature 3000K, CRI 80+
 T840 Colour temperature 4000K, CRI 80+
 DALI Driver with DALI interface and switch-control dimming
 PCA Photocell 20mm miniature type, IP65, 35 lux; 1:05 ratio

II Electric Shock protection class II
 RAL RAL colour

*note - price for uncommon RAL colour could be different from indicated. Ask before placing an order

STANDARD
