


DA-COFFEEPLANT

Park and Street Luminaires



Images for the product family and options:



Description:

Pole-mounted LED park luminaire
Light distribution type: direct
Optical system: lenses, tempered glass diffuser, impact resistant
Housing: aluminium
Colour: black grey (RAL7021)

General data:

Mains voltage: 220-240V, 0/50/60Hz
LED lifetime, h: 100000/L90B10
CFCM: 2
Protection class IEC: I (II optional)
Ingress protection code: IP65
Mechanical impact resistance: IK08
Operating temperature range, °C: ta -25...+40

Installation:


With three screws on pole Ø60mm. Push-in terminal. 3x2x2.5mm²

Environment:

Outdoor

Application:

Parking area, park, public space, street



Photocell PCA switches lighting fixtures ON or OFF, at the same time it can be mounted into IP protected light fitting serving as a standalone solution. The built-in photo-sensor records the brightness of the surroundings and switches the connected lighting fixtures on at dusk and off again at dawn. Technical data: IP65- dust and waterproof, 35 lux, 1:05 ratio. For more information see the option list

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
DA-COFFEEPLANT-425-34W-30-IP65	425	425	816	4281	34	126	70+	3000	8,2
DA-COFFEEPLANT-425-44W-30-IP65	425	425	816	5344	44.3	121	70+	3000	8,2
DA-COFFEEPLANT-425-51W-30-IP65	425	425	816	6421	51	126	70+	3000	8,2
DA-COFFEEPLANT-425-66W-30-IP65	425	425	816	8016	65.8	122	70+	3000	8,2
DA-COFFEEPLANT-425-34W-40-IP65	425	425	816	4451	34	131	70+	4000	8,2
DA-COFFEEPLANT-425-44W-40-IP65	425	425	816	5557	44.3	125	70+	4000	8,2
DA-COFFEEPLANT-425-51W-40-IP65	425	425	816	6677	51	131	70+	4000	8,2
DA-COFFEEPLANT-425-66W-40-IP65	425	425	816	8335	65.8	127	70+	4000	8,2
DA-COFFEEPLANT-425-34W-30-IP65	425	425	816	4166	34	123	70+	3000	8,2
DA-COFFEEPLANT-425-44W-30-IP65	425	425	816	5201	44.3	117	70+	3000	8,2
DA-COFFEEPLANT-425-51W-30-IP65	425	425	816	6250	51	123	70+	3000	8,2
DA-COFFEEPLANT-425-66W-30-IP65	425	425	816	7802	65.8	119	70+	3000	8,2
DA-COFFEEPLANT-425-34W-40-IP65	425	425	816	4333	34	127	70+	4000	8,2
DA-COFFEEPLANT-425-44W-40-IP65	425	425	816	5409	44.3	122	70+	4000	8,2
DA-COFFEEPLANT-425-51W-40-IP65	425	425	816	6499	51	127	70+	4000	8,2
DA-COFFEEPLANT-425-66W-40-IP65	425	425	816	8113	65.8	123	70+	4000	8,2
DA-COFFEEPLANT-425-34W-30-IP65	425	425	816	4223	34	124	70+	3000	8,2
DA-COFFEEPLANT-425-44W-30-IP65	425	425	816	5273	44.3	119	70+	3000	8,2
DA-COFFEEPLANT-425-51W-30-IP65	425	425	816	6335	51	124	70+	3000	8,2
DA-COFFEEPLANT-425-66W-30-IP65	425	425	816	7909	65.8	120	70+	3000	8,2
DA-COFFEEPLANT-425-34W-40-IP65	425	425	816	4392	34	129	70+	4000	8,2
DA-COFFEEPLANT-425-44W-40-IP65	425	425	816	5483	44.3	124	70+	4000	8,2
DA-COFFEEPLANT-425-51W-40-IP65	425	425	816	6588	51	129	70+	4000	8,2
DA-COFFEEPLANT-425-66W-40-IP65	425	425	816	8224	65.8	125	70+	4000	8,2

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. icLighting is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

T730	Colour temperature 3000K, CRI 70+
T740	Colour temperature 4000K, CRI 70+
T750	Colour temperature 5000K, CRI 70+
LS140	Optics with 140x140 beam angle
LSM1	Optics with asymmetric beam SM1, Universal road lighting
LSS1	Optics with asymmetric beam SS1
DALI	Driver with DALI interface and switch-control dimming

ADIM	Driver with autonomous two-level dimming
PCA	Photocell 20mm miniature type, IP65, 35 lux; 1:05 ratio
II	Electric Shock protection class II
Tmin-40C	Luminaire suitable for low ambient temperatures up to -40 C
RAL	RAL colour
<i>*note - price for uncommon RAL colour could be different from indicated. Ask before placing an order</i>	

