


## DA-COMMONTANSY

### Park and Street Luminaires



Images for the product family and options:



**Description:**

DA-COMMONTANSY shaped ground mounted

LED luminaire

Optical system: lenses, clear polycarbonate diffuser, impact resistant

Housing: aluminum

Colour: dark grey, RAL7043

**General data:**

Mains voltage: 220-240V, 0/50-60Hz

LED lifetime, h: 100000/L90B10

Protection class IEC: I

Ingress protection code: IP66

Mechanical impact resistance: IK08

Operating temperature range, °C: ta -25...+40

**Installation:**

On the ground+. Screw terminal. 3x1x1.5mm<sup>2</sup>

**Environment:**

Outdoor

**Application:**

Park, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*. W	System efficacy*. lm/W	CRI * (Ra)	CCT*, K	Weight, kg
DA-COMMONTANSY-168-50W-30-	168	168	3500	4300	50	86	70+	3000	31
DA-COMMONTANSY-168-50W-30-IP66	168	168	3500	4300	50	86	70+	3000	31
DA-COMMONTANSY-168-50W-40-	168	168	3500	5000	50	100	70+	4000	31
DA-COMMONTANSY-168-50W-40-IP66	168	168	3500	5000	50	100	70+	4000	31

\*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. IcLighting is constantly developing and

improving its products. The right is reserved to change any product specifications without prior notification

\*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

**Available options:**

T730      Colour temperature 3000K, CRI 70+  
 T740      Colour temperature 4000K, CRI 70+  
 LS140      Optics with 140x140° beam angle, Wide area lighting  
               such as parking lots

LSM1

Optics with asymmetric beam SM1

Driver with DALI interface and switch-control dimming

