


## DA-GILLIFLOWER

### Park and Street Luminaires



Images for the product family and options:



**Description:** Pole-mounted basic LED street luminaire

Light distribution type: direct  
 Optical system: polycarbonate asymmetric street optics, UV stabilized, impact resistant  
 Housing: aluminium  
 Colour: light grey (RAL 7042)

**General data:** Mains voltage: 220-240V, 50/60Hz

LED lifetime, h: 50000/L70B50  
 SDCM: 5  
 Protection class IEC: I  
 Ingress protection code: IP65  
 Mechanical impact resistance: IK08  
 Operating temperature range, °C: ta -20...+40

**Installation:** With two screws on 60mm horizontal or vertical pole, on the wall (mounting bracket to be ordered separately). Cable, 0.45m.  
 3x1.00mm<sup>2</sup>

**Environment:** Outdoor

**Application:** Parking area, public space


Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacv*. lm/W	CRI * (Ra)	CCT*. K	Weight, kg
DA-GILLIFLOWER-447-50W-40-IP65	447	166	72	5500	50	110	80+	4000	1
DA-GILLIFLOWER-437-30W-40-IP65	447	166	72	3600	30	120	80+	4000	1,2
DA-GILLIFLOWER-545-70W-40-IP65	545	225	72	8400	70	120	80+	4000	2,37

\*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

\*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

**Available options:**

T840 Colour temperature 4000K, CRI 80+



**Available accessories:**



Product: WALL MTG bracket (Street LED D60mm 10 P70355)

Description: Bracket for street luminaire installation onto wall, pole diameter D60mm, 10 angle, 1pcs



Product: Power supply connector - IP66/IP68, 3x1.5mm<sup>2</sup>

Description: Quick and easy to connect power supply and luminaire cables connector - IP66/IP68, 3x1.5mm<sup>2</sup>, 450V/10A, 1pcs

